

#PLASTICFREE



Slip Resistance
Maximum Category



Steel
Toecap



Anti-Perforation
Insole



Heat Resistance
up to 300°C



Anti-Static




Fuel Oil
Resistant
Outsole



S3 SRC HRO

#PLASTICFREE

COMPOSITION

UPPER	Water Resistant Genuine Leather
LINING	Full Genuine Leather Lining
TOECAP	Steel 200J EN12568:2010
INSOCK	Natural Latex w/ bio-degradable fibers and linen overlay
INSOLE	On-Protector Zero Perforation
OUTSOLE	FO HRO SRC Anti-slip Nitrilic Recycled Rubber 

STANDARD

EN ISO 20345:2011

AVAILABLE SIZES

36 to 47 EU

REMINDER


REINFORCED PROTECTION



Slip Resistance
Maximum Category



Steel Toecap



Anti-Perforation
Insole



Heat Resistance
up to 300°C







Anti-Static



Fuel Oil
Resistant
Outsole

SRC: HIGH PERFORMANCE GRIP COMBINING SRA & SRB CHARACTERISTICS

	SRA		SRB	
Surface	Ceramic floor		Steel Floor	
Lubricant	Sodium laurysulfate		Glycerine	
Foot Position				
Standard Demands	≥0,32	≥0,28	≥0,18	≥0,13

Leather safety sneakers, in conformity with the requirements of the **EN ISO 20345:2011** standard, acquiring the **S3** safety category (water resistant upper, anti-perforation insole and protection toecap). Equipped with a rubber outsole that offers greater durability, excellent slip resistance performance (**SRC**) and heat resistance up to 300°C (**HRO**).

